

45. P-4004 UNISTRUT.
46. P-4043 UNISTRUT "U" SHAPE FITTING.
47. P-4003 UNISTRUT @ EACH P-4004 POST.
48. P-1000 UNISTRUT SUPPORT.
49. PROVIDE CLOSURE STRIPS @ ALL EXPOSED UNISTRUT.
50. P-2324 UNISTRUT FLAT PL. FITTING @ T. & B. OF EACH DIAG. P-1000 UNISTRUT BRACE.
51. P-1000 UNISTRUT DIAGONAL BRACE. 1-EACH SIDE, BETWEEN EACH VERT. P-1000 SUPPORT.
52. P-1026 UNISTRUT ANGLE FITTING, WITH 1/2" DIA. BOLTS & P-1010 NUT.
53. P-1001-A3 UNISTRUT CHANNEL COMBINATION.
54. CABINET DOOR PULL. SEE SPECS.
55. 2" X 4" BLOCKING (CONTINUOUS @ CAB. FRONT & BACK). LEVEL & SHIM AS REQ'D.
56. SCREW CABINET BOTTOM TO LEVELED 2" X 4" BLOCKING.
57. SHOOT-IN FASTENERS (ANCHOR) TO FLOOR SLAB AS REQUIRED. VERIFY W/ PROJECT ARCHITECT.
58. METAL ANLE SECURED TO FLOOR AND BLOCKING.
59. INTERMEDIATE 2" X 4" WD. BLOCKING. LEVEL, SHIM, & NAIL TO CONTINUOUS FRONT & BACK BLOCKING.
60. CONTINUOUS 1/2" X 3 1/2" WATER-RESISTANT PLYWOOD @ FRONT KICK AREA.
61. NAIL PLYWOOD TO 2" X 4" BLKG. @ 24" O.C. MAXIMUM. PROVIDE MASTIC @ FLOOR CONTINUOUSLY.
62. RESILIENT BASE. SEE ARCHITECTURAL DRAWINGS.
63. CONTINUOUS DRIP WITH ACID-RESISTANT SEALER.
64. 1 5/8" UNISTRUT TIE @ 32" O.C., ANCHOR TOP & BOTTOM TO STUDS W/ TEK SCREW FASTENERS.
65. PIPING @ TIE SHOWN FOR REFERENCE ONLY. SEE PLUMBING & MECHANICAL DRAWINGS.
66. VERTICAL P-1000 UNISTRUT @ 24" O.C. @ WALL-HUNG ADJUSTABLE SHELIVING.
67. P-2494 UNISTRUT BRACKETS AS REQUIRED.
68. P-4004 UNISTRUT TOP TRACK.
69. P-1036 UNISTRUT FITTINGS, P-1026 ANGLES, & CAPS @ HUNG CASEWORK ENDS & CORNERS.
70. P-1031 UNISTRUT FITTINGS & P-1026 ANGLES AS REQUIRED @ INTERMEDIATE P-4004 SUPPORTS.
71. 3/4" P.BD. DRAWER W/ MELAMINE @ ALL SURFACES. SEE SPECS.
72. SEE CASEWORK SPECIFICATIONS FOR ALL CABINET HARDWARE & ACCESSORIES.
73. 3/8" DIA. HILTI # KB11 DROP-IN ANCHOR, WITH 2 1/2" EMBEDMENT.
74. P-1026 ANGLES NOT SHOWN IN THIS VIEW FOR CLARITY.
75. 1/4" DIA. BOLT WITH WASHERS TO CABINET STIFFENER, TYPICAL.
76. NOTCH AS REQUIRED IN BASE CABINET WOOD BLOCKING @ EACH HORIZONTAL P-1000 UNISTRUT BRACE.
77. OUTLET @ EACH SIDE OF P-4004 UNISTRUT POST. RUN CONDUIT IN POST. SEE ELECT. DWGS.
78. PLASTIC LAMINATE FINISH OVER 3/4" PLYWOOD FASCIA BOARD WITH RETURNS @ EACH END.
79. P-2492 UNISTRUT BRACKET AS REQUIRED.
80. NICKEL PLATED CHORD BRACKET WITH 2 SCREWS TO UNDERSIDE OF SHELF.
81. 18" LONG COILED CHORD WITH PLUG FROM RECESSED FLUOUERSCENT LIGHT FIXTURE. SEE ELECTRICAL DWGS.
82. 6" WIDE, 18 GAGE CONTINUOUS MOUNTING STRAP, SECURED TO METAL STUDS W/ 3 TEK SCREWS PER STUD.
83. 3/4" P.BD. WITH PLASTIC LAMINATE FINISH @ ALL SURFACES.
84. 1 1/2" P.BD. SIDE SUPPORT PANEL W/ PLASTIC LAMINATE FINISH @ ALL SURFACES.
85. RECESSED FLUSH BOLTS @ BACK SPLASH, TYPICAL.
86. 3/4" P.BD. FIXED END PANEL W/ PLASTIC LAMINATE FINISH.
87. 1 1/2" X 2 1/2" HARDWOOD EDGE W/ TONGUE.
88. DADO END OF P.BD. TOP FOR EDGING.
89. 3/4" P.BD. @ ADJACENT CASEWORK SIDE PANEL.
90. METAL SLEEVE @ EACH FLUSH BOLT STRIKE POINT.
91. ACID-RESISTANT SEAL.
92. SLIDING SAFETY GLASS DOORS W/ FINGER-PULLS @ UPPER HUNG CABINET UNITS, TYPE " ".
93. ROUTED-IN HANGING GLASS DOORS @ UPPER-HUNG CABINET UNITS, TYPE " ".
94. PLASTIC GUIDES FOR SLIDING GLASS DOORS @ UPPER-HUNG CABINET UNITS, TYPE " ".
95. CONTINUOUS 6" WIDE 18 GAGE STRAP, W/ 3 SCREWS TO EACH STUD.
96. FULL EXTENSION DRAWER GUIDES, SEE SPECS..
97. NOT USED
98. BOLT TO UNISTRUT SUPPORT @ 24" O.C. W/ MIN. 3 BOLTS PER UNIT
99. UNISTRUT P-1000 SUPPORT W/ SELF TAPPING SCREWS @ 12" O.C. TO CONT. METAL STRAP

CASEWORK DETAIL NOTES

FULL SIZE

A771-1

ARCHITECTURAL STANDARD DETAILS CASEWORK

UNIVERSITY OF CALIFORNIA - LAWRENCE BERKELEY NATIONAL LABORATORY
FACILITIES DIVISION

DRAWN BY W.C.	DETAIL TYPE SITE\STAIR
DATE 7/6/98	SCALE AS NOTED
APPROVED BY	SHEET
DATE	A771-1
DRAWING FILE NAME A771-1	1